

Defoamer BR 1150

Descriptions

Defoamer BR 1150 is a powerful defoamer designed to give foam control in a wide variety of aqueous systems. It can be easily diluted with water to give a stable dispersion for ease of application and economy of use.

Principal uses

Defoamer BR 1150 is a general purpose foam control agent suitable for use in a wide variety of emulsion based systems, including paints and adhesives.

Typical Properties

Appearance@ 25°C	Opaque yellow liquid
Density, @ 20°C	0.91 - 0.93 g/cm ³
Viscosity @ 25°C	ca 300 - 600 mPa s

Health and Safety

Detailed information on handling and any precautions to be observed in the use of the product can be found in the relevant Material Safety Data Sheet.

Approvals

FDA 175.105, 176.210,

Dosage

In paint formulations 0.1 - 0.4% on total formulation is recommended. For adhesives 0.2 - 0.3% based on the weight of latex solids is generally adequate. Defoamer BR 1150 may be incorporated as supplied or dispersed in water prior to use.

Storage and Handling

Store at temperatures between 5°C and 35°C. The product is freeze - thaw stable, however allow the material to warm to room temperature and mix well before use.

Package

Defoamer BR 1150 is available in 20kg. kegs, 180kg. steel drums, and 850kg.