

## **Multi-functional Regulating Agent AEP6280**

### **●Chemical name/composition**

Multi-functional regulating agent AEP 6280 is organic alcohol amines.

### **●Description**

Multi-functional regulating agent AEP 6280 is weak alkalinity and low volatility. It has a low smell, can replace ammonia in the coating formula, reduce the bad smell caused by ammonia volatilization; It has a certain volatility and will not remain in the paint film for a long time, so it can be used in high-gloss coatings and has excellent water resistance; It has strong wetting ability, can improve the dispersion stability of filler, adding AEP6280 coating formula can reduce the amount of wetting agent; Especially suitable for various architectural coatings, adhesives, emulsions and other water-based systems.

### **●Technical data/features (not as product specifications)**

The following is typical data and should not be considered a specification

Appearance	Brown to black liquid
effective components	80 %
Flash point(°C)	>= 93.4
Density(g/ml,25°C)	1.09
Dispersion	soluble in water

### **Advance**

- 1, excellent coating PH regulator
- 2, wetting and dispersing function, and can effectively reduce the dosage of dispersant, as wetting agent
- 3, can be used as additive, effectively reduce the low shear viscosity, improve the liquidity of the coating

●所有资料，包括配方均是真实的。但是客户必须在自己的试验室或设备上试验来确认，供应商不能做出任何承诺。客户必须遵守当地的专利法规。供货商有权对自己的产品进行改进，其规格有任何改动，恕不提前通知。

---

4 flowing property, assist in corrosion resistance performance, improve the storage stability of system

## **Application Suggestions**

Suggested dosage (wt %, in total) : 0.1-1.0% suggest that this product is added before grinding, after adding the suggestion in the last stage of the paint once mix slowly at low speed physical contact with the user, please immediately wash with water.

## **Hazard classification**

The following information: classification of hazardous materials and transportation regulations and marking of protective measures for storage and handling measures for toxicity and ecological effects in the case of accidents and fires can be found in our safety data manual.

### **● Use the information**

For safe use, please read the product information and product safety data sheet and package label before use, as well as any health and health hazard information.

### **● Storage**

When the package is complete, please store it in a dark, cool and dry place at 1-30°C. The shelf life is at least 60 months, after which please evaluate the performance before use. This product allows a small amount of soft precipitation, high speed stirring evenly will not affect the use, not used up, please close storage in time.

### **● Package**

25kg/ drum,200kg/drum

● 所有资料, 包括配方均是真实的。但是客户必须在自己的试验室或设备上进行试验来确认, 供应商不能做出任何承诺。  
客户必须遵守当地的专利法规。供货商有权对自己的产品进行改进, 其规格有任何改动, 恕不提前通知。

---